

DRIVERS

MODEL NUMBER

Lutron L3D0

FIXTURE TYPE

FEATURES

APPLICATIONS	Low Voltage Lighting
PRIMARY VOLTAGE	Universal Voltage (120V-277V)
SECONDARY VOLTAGE	24VDC
MAXIMUM WATTS	96VA (Watts)
FINISH	White
RATING	Indoor
CLASS	2
DIMMING LISTING	EcoSystem Controls (L3D0E) UL

ELECTRICAL

Hi-lume Premier 0.1% EcoSystem / 3 Wire constant voltage 24V LED driver with Soft-on, Fade-to-Black. The Hi-lume Premier 0.1% Constant Voltage Driver (L3D0E) is a high-performance LED driver capable of controlling up to 96W of 24V constant voltage loads. This driver provides smooth and continuous dimming down to 0.1% low-end. It is ideal for use with strip lighting in applications such as coves, under or over cabinet lighting and pathway lighting. The driver is UL Listed with an integrated wiring compartment and can be mounted up to 150' away from the load.

DIMMING PROTOCOL

- Continuous, flicker-free dimming from 100% to 0.1%
- Soft-on, Fade-to-Black operation for EcoSystem controls: fades smoothly between 0% and 0.1% when turned on and off for an incandescent like experience.
- PWM dimming meets IEEE1789 over the entire dimming range.
- UL Listed for United States and Canada (cULus®).
- NOM certified for Mexico.
- Field Adjustment Knob offers customer low-end light output tuning for better fixture-to-fixture matching.
- Guaranteed dimming performance when used with Lutron controls:
 - HomeWorks QS, Energi Savr Node units with EcoSystem controls, GRAFIK Eye QS with EcoSystem controls, PowPak with EcoSystem dimming modules, PowPak with EcoSystem wireless fixture controls, and Quantum systems, allowing for integration into a planned or existing EcoSystem lighting control solution.
 - Lutron 3-wire controls and interfaces.
- Protected from miswires of input power, up to 277 V[~], to EcoSystem control inputs.
- Rated lifetime of 50,000 hours at 40 °C (104 °F) ambient temperature and maximum loading. • FCC Part 15
 - Class A (277 V[~])
 - Class B (120 V[~])

NOT TO SCALE



- Case Dimensions:**
- 10.5" H x 5.5" W x 2.0" D
- Side Knockouts:**
- 4 locations: 0.5"
- Bottom Knockouts:**
- 2 locations: 0.5"

SPECIFY PRODUCT CODE


L3D0-96W24V-U

SERIES	DESCRIPTION
L3D0-96W24V-U	Lutron Hi-lume Premier 0.1% 96W

WIRING DIAGRAMS


L3D Models

3 Wire Controls



L3D Models

EcoSystem Digital Controls



CALIFORNIA ACCENT LIGHTING, INC.
2034 E. Lincoln Ave. #431, Anaheim, CA 92806
ph. 800.921.CALI (2254) or 714.535-7900 \ fx. 714.535.7902
info@calilighting.com \ calilighting.com

© CALI. All rights reserved. CALI reserves the right to make changes or withdraw specifications without prior notice.



2021.05.27 R1